

1/29/04

10/ 521.895

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 January 2004 (29.01.2004)


PCT

(10) International Publication Number  
**WO 2004/009295 A1**

- (51) International Patent Classification<sup>7</sup>: **B25B 23/00**
- (21) International Application Number:  
PCT/GB2003/003060
- (22) International Filing Date: 15 July 2003 (15.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0216902.7 19 July 2002 (19.07.2002) GB
- (71) Applicant (for UZ only): **PARRY, Simon, J.** [GB/GB];  
Forrester House, 52 Bounds Green Road, London N11 2EY (GB).
- (71) Applicant and  
(72) Inventor: **STEWART, Allister** [IE/—]; "East Ingle", 20  
East Shore Lane (BM).
- (74) Agent: **PARRY, Simon, James**; Forrester Ketley & Co.,  
Forrester House, 52 Bounds Green Road, London N11 2  
EY (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,  
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: WRENCH FOR HOLDING A BLOT OF A BOLTED CONNECTION DURING TIGHTENING OR LOOSENING



(57) Abstract: A tool (10) for use in securing a first element (1) to a second element via at least one threaded bolt (6) passing through an aperture in the first and second elements, the or each bolt having a head (7) locatable substantially adjacent the first element and a nut (19) locatable substantially adjacent the second element. The tool comprises a support structure provided with at least one formation (13) configured to engage the head (7) of the or each respective bolt, the support structure having a releasable engaging arrangement (12,15) configured to engage releasably the first element such that the or each said formation (13) engages the head (7) of the or each respective bolt (6) to prevent rotation of the or each respective bolt (6) within said apertures as the or each nut (19) is readily engaged with a respective bolt.

BEST AVAILABLE COPY

WO 2004/009295 A1

**WO 2004/009295 A1**



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

WRENCH FOR HOLDING A BOLT OF A BOLTED CONNECTION DURING TIGHTENING OR  
LOOSENING

**THE PRESENT INVENTION** relates to a tool. More particularly, the present invention relates to a tool for use in securing a first element to a second element via at least one threaded bolt passing through an aperture in the first and second elements.

It is known to secure a first element to a second element via one or more threaded bolts passing through apertures in the first and second elements; one end of the bolt having an enlarged head to bear immediately against the first element or to bear against a washer interposed between the head of the bolt and the first element wherein, from the other end of the bolt, an internally screw-threaded nut can be threadedly engaged on to the bolt and drawn up tightly to bear against the second element, or against a washer interposed between the nut and the second element. Usually, the nut has a generally hexagonal outer surface, and the head of the bolt can have either a corresponding outer hexagonal surface or can be formed as a screw head having a slot or crossed-slot formation to engage the tip of the screwdriver.

Typically, in order to tighten the nut on the or each bolt, the or each bolt is, in turn, prevented from rotation in its aperture by engagement of either a spanner or socket in the event that the head has an external hexagonal surface, or by the screw-driver, whilst the nut is screwed on to the threaded shank of a bolt by engagement with a spanner or socket. Therefore, it will be seen that it is necessary to use a separate tool on the head of the bolt and the nut of the bolt.

This method of installation is inconvenient where it is not possible for a single person simultaneously to have access to both ends of the bolt at the same time. Such an instant frequently occurs, for example, when fitting out a boat or yacht, where it is necessary to secure a fitting to the top side of a deck, in a position from where it is not convenient or possible for a single person also to have access to the underside of the deck.

It is therefore an object of the present invention to provide an improved tool for use in securing a first element to a second element via at least one threaded bolt passing through an aperture in the first and second element.

According to the present invention, there is provided a tool for use in securing a first element to a second element via at least one threaded bolt passing through an aperture in the first and second elements, the or each bolt having a head locatable substantially adjacent the first element and a nut locatable substantially adjacent the second element; the tool comprising:

a support structure provided with at least one formation configured to engage the head of the or each respective bolt; the support structure having a releasable engaging arrangement configured to engage releasably the first element such that the or each said formation engages the head of the or each respective bolt to prevent rotation of the or each respective bolt within said apertures as the or each nut is threadedly engaged with a respective bolt, wherein the support structure comprises: a plate, and a mechanism, said mechanism being configured to bear against the plate to urge the plate towards the first element when the support structure is engaged with the first element.

Conveniently, the tool has at least two of said formations.

Preferably, the tool has a plurality of said formations provided in a fixed array.

Advantageously, said support structure is configured to slidably engage said plate.

Conveniently, the said support structure is configured to engage the first element slidably.

Preferably, said releasable engaging arrangement comprises an aperture formed through the support structure, the aperture being configured to receive part of the first element therethrough.

Advantageously, said releasable engaging arrangement further comprises a locking pin configured to pass through said part of the first element and to bear against the support structure.

Conveniently, the or each said formation comprises a projection in the form of a screw-driver tip.

Preferably, the or each said formation comprises a projection in the form of a socket configured to receive the head of a respective bolt.

Advantageously, the or each said formation comprises an aperture or recess configured to receive the head of a respective bolt.

So that the invention may be more readily understood, and so that further features thereof may be appreciated, embodiments of the present invention may now be described, by way of example, with reference to the accompanying drawings in which:

4

FIGURE 1 is a perspective view of a yacht fitting for securement to the deck of a yacht;

FIGURE 2 is a perspective view from below, of a first embodiment of a tool in accordance with the present invention;

FIGURE 3 is a plan view from above of the tool illustrated in Figure 2, in use in securing the yacht fitting illustrated in Figure 1 to the deck of a yacht;


FIGURE 4 is a part-sectional side view of the tool and fitting illustrated in Figure 3;

FIGURE 5 is a perspective view of a tool in accordance with a second embodiment of the present invention;

FIGURE 6 is an end view of the tool illustrated in Figure 5; and

FIGURE 7 is a view corresponding generally to that of Figure 5, illustrating the tool illustrated in Figures 5 and 6, engaged with another yacht fitting.

Referring initially to Figure 1, there is illustrated a known yacht fitting in the form of an eye pad 1. The eye pad 1 illustrated comprises a planar base plate 2 in the form of a parallelogram. Upstanding from one surface of the base plate 2, there is provided a loop 3 which is secured at each end 4 to the base plate 2. The upstanding loop 3 therefore defines a passage 5 therethrough.



## 5

The base plate 2 is provided with a plurality of apertures therethrough, each aperture being configured to receive the threaded shank (not illustrated in Figure 1) of a respective bolt 6. In the particular arrangement illustrated in Figure 1, the base plate 2 has four apertures and so can receive four bolts, each bolt 6 having a head 7 provided with a conventional screw-driver-receiving crossed-slot recess 8.

The eye pad 1 illustrated in Figure 1 can be secured to a mounting surface such as the deck of a boat, such that the underside of the base plate 2 bears against the mounting surface, whereafter each bolt 6 is passed through a respective aperture through the base plate 2, and through a respective corresponding aligned aperture through the mounting surface, whereafter an internally-threaded nut of a type known *per se* can be threadedly engaged with the shank of each bolt and tightened against the deck or against a washer interposed between the deck and the nut.

Turning now to consider Figure 2, there is illustrated a tool 10 in accordance with a first embodiment of the present invention. The tool 10 comprises a support structure in the form of a generally rectangular support plate 11. In a central region of the support plate 11, there is provided an elongate and generally rectangular slot 12 through the support plate 11. The support plate 11, on one side thereof, carries four formations 13 in the form of screw-driver tip projections. In the particular arrangement as illustrated in Figure 2, each screw-driver tip projection 13 takes the form of a commonly known cross-head screw-driver tip, but it is equally possible for each projection 13 to take the form of other known types of tool tips such as hexagonal (allen-key) type or simple flat-bladed screw-driver tips.

## 6

Each screw-driver tip projection 13 is fixedly mounted to the support plate 11 and therefore cannot rotate with respect to the support plate 11. As will be appreciated from a comparison of Figures 1 and 2, the four projections 13 carried by the support plate 11 are provided in a diamond-shaped array corresponding to the diamond-shaped array in which the bolt-receiving apertures are provided in the base plate 2 of the eye pad 1.

Attached to the base plate 11 by a lanyard or tether 14, is a generally elongate, cylindrical locking pin 15. The locking pin 15 is provided with an internally screw-threaded transverse through-bore configured to receive the threaded shank 16 of a thumb screw 17.

Turning now to consider Figures 3 and 4, the method of operation of the tool 10 illustrated in Figure 2 will be described. Firstly, the base plate 2 (which can be considered to represent a first element) is positioned against the mounting surface or deck (which can be considered to represent a second element) in a mounting position such that each bolt-receiving aperture provided through the base plate 2 is aligned with a corresponding bolt-receiving aperture formed through the deck 18. Then, respective bolts 6 are inserted through the aligned eye pad apertures and deck apertures, such that head 7 of each bolt 6 is located substantially adjacent the uppermost surface of the base plate 2. It is to be appreciated, in this regard, that the head 7 of each bolt 6 may either be received in a countersunk aperture, may directly engage the uppermost surface of the base plate 2, or may engage a washer (provided between the uppermost surface of the base plate 2 and the undersurface of the head 7).

Once the eye pad 1 and its associated bolts 6 are mounted in position as described above, the support plate 11 of the tool 10 is positioned over the eye



7

pad 1 such that the upstanding loop 3 of the eye pad 1 is received through the elongate slot 12. It will be appreciated that because the screw-driver tip projections 13 depending from the undersurface of the support plate 11 are provided in fixed array corresponding in shape to the spaced relationship between the apertures through the base plate 2 of the eye pad 1, then each screw-driver tip 13 is configured to engage the recess 8 of a respective bolt head 7, to prevent rotation of the bolts 6 within their apertures.

In order to secure the support plate 11 in its above-mentioned operative position, the locking pin 15 is then passed through the passage 5 defined through the upstanding loop 3 of the eye pad 1, to bear against the uppermost surface of the support plate 11. The locking pin 15 can be secured in this position by rotation of the thumb screw 17 so that the end of the shank 16 of the thumb screw 17 either simply bears against the uppermost surface of the support plate 11, or is received in an internally threaded aperture or recess provided on the support plate 11.

Once the tool 10 has been installed as described above, the tool serves to prevent rotation of each bolt 6 within its apertures. Thus, it is now possible for the nuts 19 to be threadedly engaged with the shanks 20 which project through the apertures formed in the deck 18. Because the tool 10 is secured in the position illustrated in Figure 4, and prevents rotation of each bolt 6, a single person can tighten each nut 19 against the undersurface of the deck 18, or a washer interposed between the nut 19 and the deck 18, without simultaneously requiring access to the other side of the deck on which the eye pad 1 is located. After each nut 19 has been tightened in this way, the person can return to the side of the deck 18 on which the eye pad 1 is provided and unscrew the thumb screw 17, to release the locking pin 15 which can then be removed from the

loop 3, thereby permitting the support plate 11 to be lifted clear of the eye pad 1, to leave the eye pad 1 securely fastened to the deck 18.

Turning now to consider Figures 5 to 7, there is illustrated an alternative tool 30, also embodying the present invention, which is particularly configured for use in securing a length of track 31 (illustrated in Figure 7) to the deck of a boat. As illustrated in Figure 7, the track 31 is provided with a plurality of evenly-spaced apertures 32 provided along its length, each aperture 32 extending completely through the track 31 to receive a threaded bolt 33 therethrough, each bolt having a head 34. In the particular arrangement illustrated in Figure 7, each aperture 32 is countersunk and each head 34 is configured to be received in the countersunk part of each aperture 32 so that when fully engaged therewith, the upper surface of the head 34 is substantially flush with the upper surface of the track 31.

Each longitudinal side face 35 of the track 31 is provided with a longitudinal groove 36 running therealong, each longitudinal groove 36 having a generally concave cross-section.

Turning now to consider Figures 5 and 6 in more detail, the tool 30 comprises a support structure in the form of a support frame. The support frame comprises three equi-spaced supports 37, each support 37 being generally U-shaped in configuration. It will therefore be appreciated that each support 37 comprises a transverse web 38 from which a pair of spaced side limbs 39 depend. The supports 37 carry a pair of elongate support bars 40 of substantially cylindrical configuration. The support bars 40 are each secured, at positions therealong, to the free ends of the side limbs 39.

Provided between the transverse webs 38 of each support 37 and the support bars 40, is a generally rectangular support plate 41. Along each longitudinal edge 42 of the support plate 41, there are provided equi-spaced cut-outs 43 configured to slidably engage a respective side limb 39. It will therefore be appreciated that the support plate 41 is captively and slidably engaged with the support frame.

Depending from the undersurface of the support plate 41, there are provided three equi-spaced formations taking the form of conventional flat bladed screw-driver tips 44. Each screw-driver tip 44 is fixedly secured to the undersurface of the support plate 41 to prevent any rotation therebetween. However, again the formations could take the form of other types of screw-driver tips.

Each transverse web 38 of the supports 37 is provided with a threaded aperture 45 therethrough which threadably receives the threaded shank 45 of a respective bolt 46. Each bolt 46 can be provided either with a conventional bolt head 47 as illustrated, or with a thumb screw type head.

Figure 7 illustrates the tool 30 engaged with the deck track 31 (which can be considered to represent a first element), ready for use in securing the deck track 31 to a deck (which can be considered to represent a second element). The deck track 31 is slidably engaged with the support bars 40 such that each support bar 40 is slidably received within a respective longitudinal groove 36 of the deck track 31. The deck track 31 is aligned with the support structure of the tool 30 such that each screw-driver tip projection 44 is aligned with a respective bolt head 34 carried by the deck track 31.

The deck track 31 can then be placed in a mounting position against the deck to which it is to be mounted, such that each bolt 33 extends through the apertures 32 provided in the deck track 31 and through corresponding, aligned apertures provided through the deck. Thereafter, the support plate 41 can be lowered along the side limbs 39 such that each screw-driver tip projection 44 engages a respective bolt head 34. Then, the clamping bolts 46 threadedly engaged with the transverse webs 38 of each support 37 are driven downwardly such that the lowermost end of each shank 45 bears against the uppermost surface of the support plate 41 to urge the plate 41 towards the deck track 31 in a clamping manner.

When installed in this manner (as illustrated in Figure 7), the tool 30 serves to prevent rotation of the bolts 33 passing through the deck track 31 and the deck (not shown), whereafter respective nuts can be threadedly engaged with the lowermost end of the bolts 33 in a manner similar to that described in connection with the embodiment illustrated in Figures 1 to 4. After each bolt 33 engaged with a respective screw-driver tip projection 44 has had its nut fully tightened, the clamping bolts 46 can be released, thereby allowing the support plate 41 to be lifted which, in turn, permits the screw-driver tip projections 44 to be disengaged with their respective bolt heads 34. The entire tool 30 can then be moved slidably along the deck track 31 for subsequent clamping against the deck track 31 to tighten a further set of bolts 33 extending through the deck track 31. After all of the bolts 33 have been tightened, the tool 30 can be disengaged from the deck track 31 by sliding it off the end of the deck track 31.

It is to be appreciated, however, that the above-mentioned clamping mechanism of the tool 30 illustrated in Figures 5 to 7, could, instead of using the clamping bolts 46 threadedly engaged with the transverse webs 37, comprise a rotatable cam shaft mounted for rotation between the transverse

webs 38 and the support plate 41, to urge the support plate 41 towards the deck track 31 upon rotation of the cam shaft.

Also, whilst in each of the above-described embodiments of the present invention, the projections for engagement with respect mounting bolts take the form of screw-driver tips, they could, instead, take the form of sockets configured to receive engagingly the heads of the mounting bolts. Alternatively, the projections could be replaced with simple apertures or recesses formed in the support plate 11 of the arrangement illustrated in Figures 1 to 4, or the support plate 41 of the arrangement illustrated in Figures 1 to 7, each said aperture or recess being configured to receive engagingly the head of a respective mounting bolt.

In the present specification "comprises" means "includes or consists of" and "comprising" means "including or consisting of".

The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

## CLAIMS:

1. A tool for use in securing a first element to a second element via at least one threaded bolt passing through an aperture in the first and second elements, the or each bolt having a head locatable substantially adjacent the first element and a nut locatable substantially adjacent the second element; the tool comprising:

a support structure provided with at least one formation configured to engage the head of the or each respective bolt; the support structure having a releasable engaging arrangement configured to engage releasably the first element such that the or each said formation engages the head of the or each respective bolt to prevent rotation of the or each respective bolt within said apertures as the or each nut is threadedly engaged with a respective bolt, wherein the support structure comprises: a plate, and a mechanism, said mechanism being configured to bear against the plate to urge the plate towards the first element when the support structure is engaged with the first element.

2. A tool according to Claim 1, having at least two of said formations.

3. A tool according to Claim 1 or Claim 2, having a plurality of said formations provided in a fixed array.

4. A tool according to any preceding claim, wherein the support structure is configured to slidably engage said plate.

5. A tool according to any preceding claim, wherein the support structure is configured to engage the first element slidably.

6. A tool according to any one of Claims 1 to 3, wherein said releasable engaging arrangement comprises an aperture formed through the support

structure, the aperture being configured to receive part of the first element therethrough.

7. A tool according to Claim 6, wherein said releasable engaging arrangement further comprises a locking pin configured to pass through said part of the first element and to bear against the support structure.

8. A tool according to any preceding claim, wherein the or each said formation comprises a projection in the form of a screw-driver tip.

9. A tool according to any one of Claims 1 to 7, wherein the or each said formation comprises a projection in the form of a socket configured to receive the head of a respective bolt.



10. A tool according to any one of Claims 1 to 7, wherein the or each said formation comprises an aperture or recess configured to receive the head of a respective bolt.

11. A tool substantially as hereinbefore described with reference to and as shown in Figures 2 to 4.

12. A tool substantially as hereinbefore described with reference to and as shown in Figures 5 to 7.



13. Any novel combination of features disclosed herein.

1 / 5





2 / 5






FIG 5

4 / 5




FIG 6




FIG 7

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 03/03060

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 B25B23/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B25B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 593 323 A (RAPID SA) 20 April 1994 (1994-04-20) the whole document	1-5,8-10
X	US 1 900 314 A (STROM WILLIAM S) 7 March 1933 (1933-03-07) the whole document	1,8
A	US 1 412 965 A (PRIDEMORE WILLIAM H) 18 April 1922 (1922-04-18) the whole document	1-5,9,10



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

27 October 2003

Date of mailing of the international search report

05/11/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Kühn, T

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/GB 03/03060

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☒ Claims Nos.: 11-13  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:  
see FURTHER INFORMATION sheet PCT/ISA/210
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this International application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

Continuation of Box I.2

Claims Nos.: 11-13

Claims shall not rely in respect of the technical features of the invention on references to the description or drawings (Rule 6.2a PCT).

The applicant's attention is drawn to the fact that claims, or parts of claims, relating to inventions in respect of which no international search report has been established need not be the subject of an international preliminary examination (Rule 66.1(e) PCT). The applicant is advised that the EPO policy when acting as an International Preliminary Examining Authority is normally not to carry out a preliminary examination on matter which has not been searched. This is the case irrespective of whether or not the claims are amended following receipt of the search report or during any Chapter II procedure.

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 03/03060

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0593323	A	20-04-1994	FR 2697062 A1	22-04-1994
			DE 69302251 D1	23-05-1996
			DE 69302251 T2	12-12-1996
			EP 0593323 A1	20-04-1994
			ES 2087684 T3	16-07-1996
US 1900314	A	07-03-1933	NONE	
US 1412965	A	18-04-1922	NONE	



## PATENT COOPERATION TREATY



## PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT  
(PCT Article 36 and Rule 70)

REC'D 04 NOV 2004

WIPO

PCT

Applicant's or agent's file reference I16477WO		<b>FOR FURTHER ACTION</b> See Notification of Transmittal of International Preliminary Examination Report (Form PCT/PEA/416)	
International application No. PCT/GB 03/03060	International filing date (day/month/year) 15.07.2003	Priority date (day/month/year) 19.07.2002	
International Patent Classification (IPC) or both national classification and IPC B25B23/00			
Applicant STEWART, Allister et al.			
<p>1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.</p> <p>2. This REPORT consists of a total of 5 sheets, including this cover sheet.</p> <p><input type="checkbox"/> This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).</p> <p>These annexes consist of a total of sheets.</p>			
<p>3. This report contains indications relating to the following items:</p> <p>I <input checked="" type="checkbox"/> Basis of the opinion</p> <p>II <input type="checkbox"/> Priority</p> <p>III <input checked="" type="checkbox"/> Non-establishment of opinion with regard to novelty, inventive step and industrial applicability</p> <p>IV <input type="checkbox"/> Lack of unity of invention</p> <p>V <input checked="" type="checkbox"/> Reasoned statement under Rule 66.2(a)(ii) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement</p> <p>VI <input type="checkbox"/> Certain documents cited</p> <p>VII <input type="checkbox"/> Certain defects in the international application</p> <p>VIII <input type="checkbox"/> Certain observations on the international application</p>			
Date of submission of the demand  19.02.2004		Date of completion of this report  03.11.2004	
Name and mailing address of the International preliminary examining authority:   European Patent Office D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465		Authorized Officer  Kühn, T  Telephone No. +49 89 2399-7883  	

# INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/GB 03/03060

## I. Basis of the report

1. With regard to the **elements** of the international application (*Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17)*):

### Description, Pages

1-11 as originally filed

### Claims, Numbers

1-13 as originally filed

### Drawings, Sheets

1/5-5/5 as originally filed

2. With regard to the **language**, all the elements marked above were available or furnished to this Authority in the language in which the international application was filed, unless otherwise indicated under this item.

These elements were available or furnished to this Authority in the following language: , which is:

- ☐ the language of a translation furnished for the purposes of the international search (under Rule 23.1(b)).
- ☐ the language of publication of the international application (under Rule 48.3(b)).
- ☐ the language of a translation furnished for the purposes of international preliminary examination (under Rule 55.2 and/or 55.3).

3. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:

- ☐ contained in the international application in written form.
- ☐ filed together with the international application in computer readable form.
- ☐ furnished subsequently to this Authority in written form.
- ☐ furnished subsequently to this Authority in computer readable form.
- ☐ The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
- ☐ The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished.

4. The amendments have resulted in the cancellation of:

- ☐ the description, pages:
- ☐ the claims, Nos.:
- ☐ the drawings, sheets:

# INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/GB 03/03060

5. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)).

*(Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report.)*

6. Additional observations, if necessary:

## III. Non-establishment of opinion with regard to novelty, inventive step and industrial applicability

1. The questions whether the claimed invention appears to be novel, to involve an inventive step (to be non-obvious), or to be industrially applicable have not been examined in respect of:

☐ the entire international application,

☒ claims Nos. 11-13

because:

☐ the said international application, or the said claims Nos. relate to the following subject matter which does not require an international preliminary examination (specify):

☐ the description, claims or drawings (*indicate particular elements below*) or said claims Nos. are so unclear that no meaningful opinion could be formed (*specify*):

☐ the claims, or said claims Nos. are so inadequately supported by the description that no meaningful opinion could be formed.

☒ no international search report has been established for the said claims Nos. 11-13

2. A meaningful international preliminary examination cannot be carried out due to the failure of the nucleotide and/or amino acid sequence listing to comply with the standard provided for in Annex C of the Administrative Instructions:

☐ the written form has not been furnished or does not comply with the Standard.

☐ the computer readable form has not been furnished or does not comply with the Standard.

## V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Yes: Claims	6,7
	No: Claims	1-5,8-10
Inventive step (IS)	Yes: Claims	6,7
	No: Claims	1-5,8-10
Industrial applicability (IA)	Yes: Claims	1-10
	No: Claims	

2. Citations and explanations

see separate sheet

**Re Item V**

**Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**

**1. Relevant prior art**

Reference is made to the following documents:

**D1:** EP-A-0 593 323 (RAPID SA) 20 April 1994 (1994-04-20)

**D2:** US-A-1 900 314 (STROM WILLIAM S) 7 March 1933 (1933-03-07)

**2. Independent claim 1**

**2.1** Claim 1 does not meet the requirements of Article 33(2) PCT, because the subject-matter is not novel.

Document **D1** discloses (see figs.) a tool for use in securing a first element to a second element via at least one threaded bolt passing through an aperture in the first and second elements, the or each bolt having a head locatable substantially adjacent the first element and a nut locatable substantially adjacent the second element; the tool comprising:

- a) a support structure 1 provided with at least one formation 2 configured to engage the head 3 of the or each respective bolt V;
- b) the support structure having a releasable engaging arrangement 7 configured to engage releasably the first element such that each said formation engages the head of each respective bolt to prevent rotation of each respective bolt within said apertures as each nut is threadedly engaged with a respective bolt (cf. fig. 2),

wherein the support structure comprises

- c) a plate 1 and
- d) a mechanism 7 being configured to bear against the plate (\*) to urge the plate towards the first element when the support structure is engaged with the first element

- (\*) According to fig. 5, the support structure 1 is in engagement with the first element by a catch 7, whereby the intermediate portions 8 of the support structure are elastically bent towards the first element P. Due to the elastic deformation of the intermediate portions 8, the mechanism 7 inevitably bears against the plate of the support structure (cf. definition of "bear" according to The New Oxford Dictionary: "support" ) in an engaged condition of the tool when the support structure is engaged with the first element.

Therefore, **D1** discloses all the features of present claim 1 and anticipates claim 1.

**INTERNATIONAL PRELIMINARY  
EXAMINATION REPORT - SEPARATE SHEET**

---

International application No. PCT/GB 03/03060

**2.2** Furthermore, the tool according to **D2** also discloses the combination of features of claim 1. According to fig. 1 and in particular the vertical sectional view depicted in fig. 3; page 1, lines 69-75 and page 2, lines 10 and 11 the extreme edge portions 28,30 serve to constitute rest members (cf. also page 2, lines 43-57) for contacting the left hand sheet and hence for securing the two sheets between these edge portions 28,30 and the opposing leg portions 8,10.

**3. Dependent claims 2-5 and 8-10**

In view of **D1** and **D2**, these claims do not contain any features which, in combination with the features of any claim to which they refer, meet the requirements of the PCT in respect of novelty (Article 33(2) PCT).

**4. Dependent claims 6 and 7**

The additional features of claims 6 and 7 are not known in combination with the features of claims 1-3. Therefore, claims 6 and 7 meet the requirements of Article 33(2) EPC.

Since none of the the prior art documents cited in the International Search Report discloses an aperture formed through the support structure of the tool which is adapted for receiving a hook shaped member of a first element, the subject-matter of claims 6 and 7 is not obvious (Article 33(3) PCT).

**5. Industrial applicability**

~~Since the tool for securing a first element to a second element according to claim 1~~  
can be made and used in industry, claim 1 meets the requirements of Article 33(4) PCT.

Dependent claims 2-10 define embodiments of the tool according to claim 1. Therefore, they also meet the requirements of Article 33(4) PCT.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**